

Battery Charger CHRG-2590



Allows for the charging of up to **6 BB-2590 batteries** at the same time.

Advantages:

- Hot-Swap possibility.
- Charging time does not depend on the number of plugged-in batteries.
- Optimized charging cycle, implemented according to the battery manufacturer's recommendations.
- Build-in charging temperature control.
- Built-in GUI displaying crucial parameters of each battery, including:
 - Current charge level
 - Remaining charging time
 - Updated battery capacity
 - Number of registered charging cycles
- Optional, built-in USB charger (2x A-type USB).
- Standard suitcase (different colors to choose from).



CHRG-2590 technical specification

Environmental

Standard compliance	MIL-STD 810
Operating temperature range	0°C to 50°C (32°F to 122°F)
Storage temperature range	-40°C to 60°C (-40°F to 140°F)
IP rating	IP67 (not charging)

Mechanical parameters

Size	47.4 cm x 41.5 cm x 21.4 cm (18,66 in x 16,34 in x 8,43 in)
Weight	8.5 kg
Color options	Black, Sand, Olive green, Orange, Navy, Yellow

Electrical

Power input	80 – 240 VAC, 45 – 63 Hz
Maximum power consumption	900 W
Maximum charging current	3A (for each BB-2590 battery cell)
Maximum current for USB charging	600 mA



Global Infrastructure & Security Solutions

GISS Sp. z o.o., ul. Kościuszkowców 63, 04-545 Warszawa
T: +48 22 625 09 52 | F: +48 22 613 01 42 | VoIP: +48 22 349 93 92 | E: info@giss.pl